

Profile Selection Guide



Compression Seal

Schlegel EMI is a trusted name in gasket forming and wrapping. We have over 100 years of experience. We offer various types of foams to meet your application needs, all halogen free. Cladding colors come in a variety.

All parts shipped from Schlegel EMI are RoHS and REACH compliant



PolyFab Properties



Highly engineered embossed polyethylene liner

- Resists paints and varnishes
- Long lasting
- Maintains an attractive appearance



UV stabilized

- Stable in sunlight (UV stable)
- Tested up to 5,000 Kj/m² with no visible degradation



Resilient urethane open-celled foam

- Shape and resiliency are retained over time
- Offers excellent all temperature sealing performance
- No corner leaks
- Seal conforms to uneven surfaces



Dual durometer insert

- Allows for easy insertion and maximum retention
- It is removable without damaging jamb or seal

Part Number Guide



Foam: 1: Grey / 5: Green

Liner

Black	White	Brown	Beige	Grey	Black (Fine Satin Embossed)*	

^{*}Black (Fine Satin Embossed):

Hydrostatic Resistance: 115psi. Flame Resistance, after flame: (sec) ≤ 2.0

Attachment: with tape "T" or without tape "-"

Length: reeled or cut-to-length

Tensile Strength (psi)	3450	
Compression Set	<15% (compressed at 50% during 22 Hrs.@ 70℃)	
Heat Conductivity W/mK	0.06 at 0 °C	
Operating Temperature	-60 to 70℃	

Profiles

P4U	P66	P4E	P63	P68		
1						
		₫Þ				
2.54mm x 6.6mm	6.35mm x 9.53mm	6.6mm x 6.6mm	9.53mm x 9.53mm	9.53mm x 12.7mm		
.100" x .260"	.250" x .375"	.260" x .260"	.375" x .375"	.375" x .500"		
P90	P10	P4P	P41	P4T		
3.56mm x 6.35mm	6.35mm x 9.53mm	3.8mm x 4.8mm	5.08mm x 4.83mm	5.1mm x 6.9mm		
.140" x .250"	.250" x .375"	.150" x .189"	.200" x .190"	.201" x .272"		
P4S	PQ2	P4R	P53	P4Q		
F43	r Q2	F4N	F 33	740		
	\cap	\cap	\cap	\bigcirc		
			<u> </u>	\		
				<u> </u>		
5.7mm x 4.8mm	6.35mm x 4.83mm	6.4mm x 6.9mm	7.62mm x 6.86mm	9.53mm x 4.83mm		
.224" x .189"	.250" x .190"	.252" x .272"	.300" x .270"	.375" x .190"		
P3W	PH3	P98	P85	P4C		
				^		
_		_				
			//			
			//			
				45		
9.53mm x 6.86mm	8.0mm x 8.0mm	9.78mm x 10.67mm	11.8mm x 10.7mm	12.42mm x 15.06mm		
.375" x .270"	.315" x .315"	.385" x .420"	.465" x .421"	.489" x .593"		
P32	P3X	P5A	P3Y	P60		
	/ /					
/)						
			((
	_]/					
		~				
17.15mm x 14.73mm	18.79mm x 15.62mm	19.5mm x 16.6mm	23.52mm x 15.77mm	3.3mm x 13.2mm		
.675" x .580"	.740" x .615"	.768" x .654"	.926" x .621"	.130" x .520"		
P4F	P4Y		P5B			
14.7mm × 9.5mm	0.60mm v 24.0mm		E E4mm v 40 0mm			
14.7mm x 8.5mm .579" x .335"	9.68mm x 24.0mm .381" x .945"	5.54mm x 42.9mm .218" x 1.689"				
.070 1.000	.301 X .343	.210 X 1.003				





NORTH AMERICA

Schlegel Electronic Materials, Inc.

1600 Lexington Ave Suite 236A Rochester NY 14606

Tel No: +1 585-643 2000 Fax No: +1 585-427 7216

Email: schlegelemi.na@schlegelemi.com

EUROPE

Schlegel Electronic Materials, byba

Slijpesteenweg 28 8432 Middelkerke (Leffinge)

Belgium

Tel No: +32 59 560 270 Fax No: +32 59 560 271

Email: schlegelbe@schlegelemi.com

ASIA

Schlegel Electronic Materials Asia Limited

Unit 3, 3/F., Block A, New Trade Plaza, 6 On Ping Street, Shatin, N.T., Hong Kong

Tel No: +852-2686 9872 Fax No: +852-2686 9728

Email: schlegelemi@emeigroup.com

Schlegel (Dongguan) Electronics Limited

No. 8 Qiaoxin Road, Qiaotou, Dongguan,

Guangdong, China Postal Code: 523525 Tel No: +86-769-8356 5686 Fax No: +86-769-8334 5656

Email: schlegelemi@emeigroup.com

Schlegel (Shanghai) Electronics Limited

4/F., 79 Parts, 111 Meisheng Road, F.T.Z., Pudong, Shanghai, China

Postal Code: 200131 Tel No: +86-21-5868 3383 Fax No: +86-21-5868 3386

Email: schlegelemi@emeigroup.com

Taiwan Schlegel Electronics Limited

No. 99, Alley 3, Lane 182, Section 2 Wenhua Road,

Banqiao District Postal Code: 22044 Tel No: +886-2-8258 5148 Fax No: +886-2-8258 5149

Email: schlegelemi@emeigroup.com



polyfabfeedback@schlegelemi.com



www.linkedin.com/company/schlegelemi

www.schlegelemi.com